SAFETY DATA SHEET

United States



Somos® GP Plus

Section 1. Identification

GHS product identifier Other means of identification : Somos® GP Plus: Not available.

Product type : Liquid.

Material uses : Stereolithography resins for the creation of three-dimensional models and prototypes directly

from digital data.

DSM Desotech Inc.

nom digital data.

1122 St Charles Street Elgin IL 60120 Tel: +1 (847) 697-0400

e-mail address of person responsible for this SDS

: DSMRESINS.SDS@dsm.com

(Communication in English only please)

Emergency telephone

number

Supplier

: DSM Desotech Inc.: +1 (847) 697-0401 (During normal business hours)

CHEMTREC (within the USA): (800)

424-9300 (24 hour)

CHEMTREC (International): +1 (703)

527-3887 [USA] (24 hour)

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29

CFR 1910.1200).

Classification of the SKIN IRRITATION - Category 2 substance or mixture EYE IRRITATION - Category 2A

SKIN SENSITIZATION - Category 1

GHS label elements

Hazard pictograms



Signal word : Warning

Hazard statements : **▶**315 - Causes skin irritation.

H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation.

Precautionary statements

Prevention : ₱280 - Wear protective gloves: < 1 hour (breakthrough time): (0.12 mm) Nitrile gloves..

Wear eye or face protection. P261 - Avoid breathing vapor.

P264 - Wash hands thoroughly after handling.

P272 - Contaminated work clothing must not be allowed out of the workplace.

Response : \overrightarrow{P} 362 + P364 - Take off contaminated clothing and wash it before reuse.

P363 - Wash contaminated clothing before reuse.

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.

P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention. P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 - If eye irritation persists: Get medical advice or attention.

Storage : Not applicable.

Date of issue/Date of revision: 31 July 2020 Version: 4 Page: 1/16



Disposal : P501 - Dispose of contents and container in accordance with all local, regional, national

and international regulations.

Hazards not otherwise

classified

: None known.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Other means of identification : Not available.

CAS number : Not applicable.

Ingredient name	%	CAS number
Monomer	50 - 100	-
Monomer	10 - 25	-
Multifunctional Acrylate	5 - 10	-
Multifunctional Acrylate	1 - 5	-
Multifunctional Acrylate	1 - 5	-
Additive	1 - 5	-
antimony compounds	1 - 5	-
antimony compounds	1 - 5	-
Siloxane	0.1-1	-

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids.

Check for and remove any contest leaves. Cost investor at least 10 minutes. Cost

Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get

medical attention.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not

breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash

contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly

before reuse.

Ingestion : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep

at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen

tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye irritation.

Date of issue/Date of revision: 31 July 2020 Version: 4 Page: 2/16



: No known significant effects or critical hazards. Inhalation

Skin contact : Causes skin irritation. May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eve contact : Adverse symptoms may include the following:

pain or irritation

watering redness

Inhalation : No specific data.

Skin contact Adverse symptoms may include the following:

> irritation redness

Ingestion : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities

have been ingested or inhaled.

Specific treatments : No specific treatment.

Protection of first-aiders No action shall be taken involving any personal risk or without suitable training. It may be

dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products

Decomposition products may include the following materials:

carbon dioxide carbon monoxide sulfur oxides metal oxide/oxides silicium oxides (dense) black smoke aldehydes

organic acids

halogenated compounds

Special protective actions

for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment :

for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing

apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Version: 4 Date of issue/Date of revision: 31 July 2020 Page: 3/16



Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store between the following temperatures: 15 to 30°C (59 to 86°F). Store in accordance with local regulations. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Store in original container, protected from direct sunlight. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Keep away from heat and direct sunlight.

Date of issue/Date of revision: 31 July 2020 Version: 4 Page: 4/16



Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Monomer	None.
Monomer	None.
Multifunctional Acrylate	None.
Multifunctional Acrylate	None.
Multifunctional Acrylate	None.
Additive	None.
antimony compounds	ACGIH TLV (United States, 3/2019).
	TWA: 0.5 mg/m³, (as Sb) 8 hours.
	OSHA PEL 1989 (United States, 3/1989).
	TWA: 0.5 mg/m³, (as Sb) 8 hours.
	NIOSH REL (United States, 10/2016).
	TWA: 0.5 mg/m³ 10 hours.
	OSHA PEL (United States, 5/2018).
	TWA: 0.5 mg/m³, (as Sb) 8 hours.
antimony compounds	ACGIH TLV (United States, 3/2019).
	TWA: 0.5 mg/m³, (as Sb) 8 hours.
	OSHA PEL 1989 (United States, 3/1989).
	TWA: 0.5 mg/m³, (as Sb) 8 hours.
	OSHA PEL (United States, 5/2018).
	TWA: 0.5 mg/m³, (as Sb) 8 hours.
	NIOSH REL (United States, 10/2016).
	TWA: 0.5 mg/m³ 10 hours.
Siloxane	None.

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove

manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. < 1 hour (breakthrough time): (0.12 mm)

Nitrile gloves.

Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Date of issue/Date of revision: 31 July 2020 Version: 4 Page: 5/16



Other skin protection Appropriate footwear and any additional skin protection measures should be selected

based on the task being performed and the risks involved and should be approved by a

specialist before handling this product.

Based on the hazard and potential for exposure, select a respirator that meets the Respiratory protection

> appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Remarks Wear nitrile or other chemical resistant gloves to avoid skin contact when handling partially

cured fabricated objects in the "green" state of cure (after initial laser cure). The fabricated objects may be handled without gloves after the object has been thoroughly washed with solvent (e.g. tripropylene glycol monomethyl ether, isopropyl alcohol) followed by exposure to UV light and/or an oven bake at temperatures above 130°C. When sanding fully cured surfaces, suitable respiratory protection for dust should be used. Good general ventilation is required when tooling or sanding to avoid inhalation of particulate matter or airborne particles. Avoid sanding or finishing parts that are not fully cured, as uncured material may

cause skin sensitisation or respiratory irritation.

Section 9. Physical and chemical properties

Appearance

Physical state : Liquid. [viscous]

Color : White

Odor : Characteristic. Odor threshold Not available. рΗ : Not available. **Melting point** : Not available. **Boiling point** : Not available.

Flash point : Closed cup: >212°F (>100°C) [(estimate)]

Evaporation rate : Not available Flammability (solid, gas) Not available. Lower and upper explosive : Not available.

(flammable) limits

Vapor pressure : Not available. Vapor density : Not available. : 1.06 (Water = 1) Relative density : 1.06 g/cm3 (23°C) Density (g/cm³) **Bulk density** Not available. Solubility Not available. Solubility in water : Not available. Solubility at room : Not available.

temperature

Partition coefficient: n-

octanol/water

: Not available.

Auto-ignition temperature : Not available. **Decomposition temperature** : Not available.

Dynamic (room temperature): 289 to 388 mPa·s (289 to 388 cP) Viscosity

Kinematic (room temperature): >1.88 cm²/s (>188 cSt) Kinematic (40°C (104°F)): >0.205 cm²/s (>20.5 cSt)

Version: 4 Date of issue/Date of revision: 31 July 2020 Page: 6/16



Section 10. Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : Keep away from heat and direct sunlight.

Incompatible materials : No specific data.

Hazardous decomposition

products

: No specific data.

Remarks : Keep away from heat and direct sunlight.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Monomer	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat - Female	2000 mg/kg	-
Monomer	LD50 Oral	Rat - Male,	>2000 mg/kg (-
		Female	LD0 = 2000 mg/	
			kg)	
Multifunctional Acrylate	LC0 Inhalation Dusts and mists	Rat - Male,	2 mg/l	4 hours
		Female		
	LC50 Inhalation Dusts and mists	Rat - Male,	>2 mg/l	4 hours
		Female		
	LD50 Dermal	Rat - Male,	>2000 mg/kg (-
		Female	LD0 = 2000 mg/	
			kg)	
	LD50 Oral	Rat - Male,	>5000 mg/kg (-
		Female	LD0 = 5000 mg/	
			kg)	
Multifunctional Acrylate	LD50 Dermal	Rat - Male,	>2000 mg/kg (-
		Female	LD0 2000 mg/kg)	
	LD50 Oral	Rat - Female	>2000 mg/kg (-
			LD0 2000 mg/kg)	
Additive	LD50 Dermal	Rabbit - Male,	>2000 mg/kg	-
		Female		
	LD50 Oral	Rat - Male,	>5000 mg/kg	-
		Female		
antimony compounds	LD50 Oral	Rat	>5000 mg/kg	-
antimony compounds	LD50 Oral	Rat	>5000 mg/kg	-
Siloxane	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-

Irritation/Corrosion

Date of issue/Date of revision: 31 July 2020 Version: 4 Page: 7/16



Product/ingredient name	Result	Species	Score	Exposure	Observation
Monomer	Skin - Primary dermal irritation index (PDII)	Rabbit	0.8	4 hours 0.5 ml	72 hours
	Eyes - Non-irritating	Rabbit	1	1 hours 0.1 ml	72 hours
Monomer	Skin - Erythema/Eschar	Rabbit	li	4 hours 0.5 ml	24 to 72 hours
IVIOLIOITIEI	Skin - Edema	Rabbit	o	4 hours 0.5 ml	
	Eyes - Cornea opacity	Rabbit	1	0.1 ml	24 to 72 days
	Eyes - Iris lesion	Rabbit	0	0.1 ml	24 to 72 days
	Eyes - Redness of the conjunctivae	Rabbit	3	0.1 ml	24 to 72 hours
	Eyes - Edema of the conjunctivae	Rabbit	3	0.1 ml	24 to 72 hours
Multifunctional Acrylate	Skin - Moderate irritant	Mammal -	-	-	-
		species unspecified			
	Even Irritant	Mammal -			
	Eyes - Irritant		-	-	-
		species			
		unspecified			
	Respiratory - Irritant	Mammal -	-	=	-
		species			
		unspecified			
Multifunctional Acrylate	Skin - Edema	Rabbit	0.3	4 hours 0.5 ml	24 to 72 hours
1	Skin - Erythema/Eschar	Rabbit	0.96	4 hours 0.5 ml	24 to 72 hours
	Skin - Primary dermal	Rabbit	0	4 hours	_
	irritation index (PDII)	rabbit	ľ	T Hours	
	Eyes - Cornea opacity	Rabbit	0	0.1 ml	24 to 72 hours
		Rabbit	0	0.1 ml	24 to 72 hours
	Eyes - Iris lesion		-	-	
	Eyes - Redness of the conjunctivae	Rabbit	0.22	0.1 ml	24 to 72 hours
	Eyes - Edema of the conjunctivae	Rabbit	0.11	0.1 ml	24 to 72 hours
	Eyes - Mild irritant	Rabbit	-	-	-
Multifunctional Acrylate	Skin - Non-irritating	Rabbit	0	4 hours 0.5 ml	24 to 72 hours
1	Eyes - Non-irritating	Rabbit	0	0.1 ml	24 to 72 hours
Additive	Eyes - Irritant	Rabbit	1_	_	_
	Skin - Non-irritating	Rabbit	0	_	_
antimony compounds	Skin - Erythema/Eschar	Rabbit	0.8	4 hours 0.5 g	24 to 72 hours
antimony compounds	Skin - Edema	Rabbit	0.0	4 hours 0.5 g	24 to 72 hours
		Rabbit	0	0.1 ml	24 to 72 hours
	Eyes - Cornea opacity		-	-	
	Eyes - Iris lesion	Rabbit	0	0.1 ml	24 to 72 hours
	Eyes - Redness of the conjunctivae	Rabbit	1.43	0.1 ml	24 to 72 hours
	Eyes - Redness of the conjunctivae	Rabbit	0.7	0.1 ml	24 to 72 hours
antimony compounds	Skin - Erythema/Eschar	Rabbit	0.8	4 hours 0.5 g	4 hours
antimony compounds	Skin - Edema	Rabbit	0	4 hours 0.5 g	4 hours
	Eyes - Cornea opacity	Rabbit	0	0.1 ml	24 to 72 hours
	Eyes - Comea opacity Eyes - Iris lesion	Rabbit	0	0.1 ml	24 to 72 hours
			-	•	
	Eyes - Redness of the	Rabbit	1.43	0.1 ml	24 to 72 hours
	conjunctivae		l		
	Eyes - Edema of the	Rabbit	0.7	0.1 ml	24 to 72 hours
	conjunctivae	l., .			
Siloxane	Skin - Irritant	Mammal - species	-	-	-
		unspecified			
	Eyes - Irritant	Mammal -	_	_	_
		species			
		unspecified			
		unapeomed			

Sensitization



Product/ingredient name	Route of exposure	Species	Result
Monomer	skin	Mouse	Sensitizing
Monomer	skin	Guinea pig	Not sensitizing
Multifunctional Acrylate	skin	Mammal - species unspecified	Sensitizing
Multifunctional Acrylate	skin	Mouse	Sensitizing
-	skin	Guinea pig	Sensitizing
Multifunctional Acrylate	skin	Mouse	Sensitizing
antimony compounds	skin	Guinea pig	Sensitizing
antimony compounds	skin	Guinea pig	Sensitizing
Siloxane	skin	Mammal - species unspecified	Sensitizing

Mutagenicity

Product/ingredient name	Test	Experiment	Result
Monomer	-	Experiment: In vitro Subject: Mammalian-Animal	Positive
	-	Experiment: In vitro Subject: Bacteria	Negative
Monomer	OECD 471 Bacterial Reverse Mutation Test	Experiment: In vitro Subject: Bacteria Metabolic activation: Without & with	Negative
	OECD 476 <i>In vitro</i> Mammalian Cell Gene Mutation Test	Experiment: In vitro Subject: Mammalian-Animal Cell: Somatic	Negative
Multifunctional Acrylate	OECD 471 Bacterial Reverse Mutation Test	Metabolic activation: Without & with Experiment: In vitro Subject: Bacteria Metabolic activation: Without & with	Negative
	OECD 476 <i>In vitro</i> Mammalian Cell Gene Mutation Test	metrabolic activation Experiment: In vitro Subject: Mammalian-Animal Cell: Somatic Metabolic activation: Without & with	Negative
	OECD 474 Mammalian Erythrocyte Micronucleus Test	metrabolic activation Experiment: In vivo Subject: Mammalian-Animal	Negative
	OECD 474 Mammalian Erythrocyte Micronucleus Test	Experiment: In vivo Subject: Mammalian-Animal	Negative
Multifunctional Acrylate	Mammalian cell gene mutation assay	Experiment: In vitro Subject: Mammalian-Animal Cell: Somatic Metabolic activation: Without	Positive
	Mammalian cell gene mutation assay	Experiment: In vitro Subject: Mammalian-Animal Cell: Somatic Metabolic activation: With	Negative
	Mammalian cell gene mutation assay	Experiment: In vivo Subject: Mammalian-Animal	Negative
Additive	OECD 471 Bacterial Reverse Mutation Test	Experiment: In vitro Subject: Bacteria Metabolic activation: Without & with	Negative
	OECD 482 Genetic Toxicology: DNA Damage and Repair, Unscheduled DNA Synthesis in Mammalian Cells in vitro	Experiment: In vitro Subject: Mammalian-Animal Cell: Somatic Metabolic activation: Without & with	Negative
	OECD 482 Genetic Toxicology: DNA Damage and Repair,	Experiment: In vivo Subject: Mammalian-Animal	Negative

Date of issue/Date of revision: 31 July 2020 Version: 4 Page: 9/16



Unscheduled DNA Synthesis in Mammalian Cells <i>in vitro</i>		
--	--	--

Carcinogenicity

Product/ingredient name	Result	Species	Dose	Exposure
	Negative - Dermal - NOAEL	Mouse - Male	100 mg/kg /day 100 mg/kg /day 15 mg/kg /day	- - -

Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Development toxin	Species	Dose	Exposure
Multifunctional Acrylate	-	Negative	-	Rat - Male, Female	Oral: 1000 mg/kg / day NOAEL - Highest tested dose)	-
	-	-	Negative	Rat - Female	Oral: >250 mg/kg / day (NOAEL)	-
Multifunctional Acrylate	-	Negative	-	Rat - Male, Female	Oral: 750 mg/kg / day (NOEL)	-
	-	-	Negative	Rabbit - Male, Female	Oral: 180 mg/kg / day (NOAEL)	-
	-	-	Negative	Rat	Oral: 180 mg/kg / day (NOAEL)	-
Additive	-	Negative	-	Mouse - Male, Female	Oral: 10100 mg/ kg /day	-
	-	Negative	-	Mouse - Male, Female	Oral: 10100 mg/ kg /day	-

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name		Route of exposure	Target organs
Multifunctional Acrylate	Category 3		Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes of exposure

: Not available.

Potential acute health effects

Date of issue/Date of revision: 31 July 2020 Version: 4 Page: 10/16



Eye contact : Causes serious eye irritation.

Inhalation : No known significant effects or critical hazards.

Skin contact : Zauses skin irritation. May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation : No specific data.

Skin contact : Adverse symptoms may include the following:

irritation redness

Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Product/ingredient name	Result	Species	Dose	Exposure
Monomer	Sub-acute NOEL Oral	Rat - Male, Female	1000 mg/kg day	-
Multifunctional Acrylate	Sub-acute NOAEL Oral	Rat - Male, Female	1000 mg/kg /day (Highest tested dose)	-
Multifunctional Acrylate	Sub-chronic NOAEL Oral	Rat - Male, Female	50 mg/kg /day	-
Additive	Sub-chronic NOEL Dermal Sub-chronic NOEL Dermal Sub-chronic NOAEL Oral	Rat - Female Mouse - Male Rat - Male,	10 mg/kg /day 100 mg/kg /day >5000 mg/kg /day	- - 90 days; 5 days
/ tadiave		Female		per week
	Sub-chronic NOAEC Inhalation Dusts and mists	Rat - Male, Female	1000 mg/m³	93 days; 6 hours per day 5 days per week

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very

low levels.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates



Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/ I)
Somos® GP Plus	3226.1	4051.8	N/A	N/A	N/A
Monomer	2000	2500	N/A	N/A	N/A
Additive	N/A	2500	N/A	N/A	N/A
Siloxane	2500	2500	N/A	N/A	N/A

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Monomer	EC50 >100 mg/l	Algae	72 hours
	Acute EC50 18.3 mg/l	Daphnia	48 hours
	Acute LC50 11.5 mg/l	Fish	96 hours
	Acute NOEC 10 mg/l	Daphnia	48 hours
Monomer	Acute EC50 6420 mg/l Fresh water	Algae	72 hours
	Acute EC50 6910 mg/l Fresh water	Daphnia	48 hours
	Acute LC50 7500 mg/l Fresh water	Fish	96 hours
Multifunctional Acrylate	Acute EC50 11 mg/l Fresh water	Algae	72 hours
-	Acute EC50 37 mg/l Fresh water	Daphnia	48 hours
	Acute LC50 2.7 mg/l Fresh water	Fish	96 hours
Multifunctional Acrylate	NOEC 0.3 mg/l Fresh water	Daphnia	21 days
	Acute EC50 >11 mg/l Fresh water	Algae	72 hours
	Acute EC50 1.7 mg/l Fresh water	Daphnia	48 hours
	Acute LC50 1.2 mg/l Fresh water	Fish	96 hours
Additive	Acute EC50 >900 mg/l Fresh water	Algae	72 hours
	Acute EC50 >1000 mg/l Fresh water	Daphnia	48 hours
	Acute LC50 >1000 mg/l Fresh water	Fish	96 hours
antimony compounds	Acute EC50 0.044 mg/l Fresh water	Algae	72 hours
	Acute EC50 0.68 mg/l Fresh water	Daphnia	48 hours
	Acute LC50 12.6 mg/l Fresh water	Fish	96 hours
antimony compounds	Acute EC50 0.68 mg/l Fresh water	Daphnia	48 hours
	Acute LC50 0.044 mg/l Fresh water	Algae	72 hours
	Acute LC50 12.6 mg/l Fresh water	Fish	96 hours

Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
Monomer	-	0.1 % - Not readily - 28 days	-	-
Monomer	OECD 302B Inherent Biodegradability: Zahn-Wellens/	<1 % - 28 days	-	-
	EMPA Test OECD 301B Ready Biodegradability - CO ₂ Evolution	<1 % - 28 days	-	-
Multifunctional Acrylate	Test OECD 301F Ready Biodegradability - Manometric	28 % - 5 days	-	-
Additive	Respirometry Test OECD 301B Ready	69.3 % - Readily - 9 days	-	Activated sludg

Date of issue/Date of revision: 31 July 2020 Version: 4 Page: 12/16



	Biodegradability - CO ₂ Evolution Test		
Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Monomer Monomer Multifunctional Acrylate Additive antimony compounds antimony compounds	- - - -	- - - - -	Not readily Not readily Not readily Readily Not readily Not readily Not readily

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Monomer	0.6	-	low
Multifunctional Acrylate	2.41 to 3.87	-	low
Multifunctional Acrylate	2.64 to 3.78	31	low
Additive	-0.48	-	low
antimony compounds	≥2.61	-	low
antimony compounds	≥2.61	-	low

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	IMDG	IATA
UN number	Not regulated.	UN3082	UN3082	UN3082	UN3082
UN proper shipping name	-	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Poly[oxy(methyl- 1,2-ethanediyl)], alpha,alpha'- (2,2-dimethyl- 1,3-propanediyl)bis [omega-[(1-oxo- 2-propen-1-yl)oxy]-,	©UBSTANCIA LIQUIDA POTENCIALMENTE PELIGROSA PARA EL MEDIO AMBIENTE, N.E.P. (Poly[oxy(methyl- 1,2-ethanediyl)], alpha,alpha'- (2,2-dimethyl- 1,3-propanediyl)bis	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Poly[oxy(methyl- 1,2-ethanediyl)], alpha,alpha'- (2,2-dimethyl- 1,3-propanediyl)bis [omega-[(1-oxo- 2-propen-1-yl)oxy]-	Environmentally hazardous substance, liquid, n. o.s. (Poly[oxy (methyl-1,2-ethanediyl)], alpha,alpha'-(2,2-dimethyl-1,3-propanediyl)bis [omega-[(1-oxo-2-propen-1-yl)oxy]-,

Date of issue/Date of revision: 31 July 2020 Version: 4 Page: 13/16



		reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight ≤ 700))	[omega-[(1-oxo- 2-propen-1-yl)oxy]-, reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight ≤ 700))	, reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight ≤ 700))	reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight ≤ 700))
Transport hazard class(es)	-	9	9	9	0
Packing group	-	Ш	III	III	III
Environmental hazards	No.	Yes.	Yes.	Yes.	Yes.

Additional information

TDG Classification Product classified as per the following sections of the Transportation of Dangerous Goods

Regulations: 2.43-2.45 (Class 9), 2.7 (Marine pollutant mark).

Non-bulk packages of this product are not regulated as dangerous goods when transported by road or rail.

Explosive Limit and Limited Quantity Index 5

Special provisions 16, 99

Mexico Classification : The environmentally hazardous substance mark is not required when transported in sizes

of ≤5 L or ≤5 kg.

Special provisions 274, 331, 335

IMDG : This product is not regulated as a dangerous good when transported in sizes of \leq 5 L or \leq 5

kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to

4.1.1.8.

Emergency schedules F-A, S-F Special provisions 274, 335, 969

IATA : This product is not regulated as a dangerous good when transported in sizes of \leq 5 L or \leq 5

kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and

5.0.2.8.

Quantity limitation Passenger and Cargo Aircraft: 450 L. Packaging instructions: 964. Cargo Aircraft Only: 450 L. Packaging instructions: 964. Limited Quantities - Passenger

Aircraft: 30 kg. Packaging instructions: Y964.

Special provisions A97, A158, A197

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright

and secure. Ensure that persons transporting the product know what to do in the event of

an accident or spillage.

Transport in bulk according

to IMO instruments

: Not available.

Version: 4 Date of issue/Date of revision: 31 July 2020 Page: 14/16



Section 15. Regulatory information

U.S. Federal regulations : United States inventory (TSCA 8b): All components are listed or exempted.

Plean Water Act (CWA) 307: toluene; antimony compounds; antimony compounds;

benzene

Clean Water Act (CWA) 311: toluene; benzene

	Product/ingredient name	CAS#	%
Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)	antimony compounds	108-88-3 71449-78-0 89452-37-9 71-43-2	0.0037935 1.0575 1.0575 0.000018

Clean Air Act Section 602

Class I Substances

Clean Air Act Section 602

Class II Substances

: Not listed

: Not listed

DEA List I Chemicals

(Precursor Chemicals)

DEA List II Chemicals

(Essential Chemicals)

.

: Not listed

: Not listed

SARA 313

	Product name	CAS number	%
I of the ix - ixeporting	antimony compounds		Proprietary Proprietary
	antimony compounds antimony compounds		Proprietary Proprietary

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts : The following components are listed: antimony compounds

New York : None of the components are listed.

New Jersey: The following components are listed: antimony compounds; antimony compoundsPennsylvania: The following components are listed: antimony compounds; antimony compounds

California Prop. 65

MARNING: This product can expose you to chemicals including Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. This product can expose you to chemicals including Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Ingredient name		Maximum acceptable dosage level
F oluene	-	Yes.
Benzene	Yes.	Yes.
E pichlorohydrin	Yes.	-

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Ingredient name	List name	Status
Not listed.		

Date of issue/Date of revision: 31 July 2020 Version: 4 Page: 15/16



Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Ingredient name	List name	Status
Not listed.		

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Ingredient name	List name	Status
Not listed.		

International lists

Canada inventory : Not determined.

Section 16. Other information

History

Code : 015847WW39128

Date of printing : 7/31/2020

Date of issue/Date of : 7/31/2020

revision

Date of previous issue : 8/24/2018

Version : 4

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available SGG = Segregation Group UN = United Nations

Procedure used to derive the classification

Classification	Justification
KIN IRRITATION - Category 2	Calculation method
EYE IRRITATION - Category 2A	Calculation method
SKIN SENSITIZATION - Category 1	Calculation method

References : Not available.

▼ Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. While this information has been prepared in good faith by technical experts within the above named organization, the final determination of suitability of any material is the sole responsibility of the end user, after proper consultation with the end users' engineering, technical, health and safety professionals. All materials may present unknown hazards, and should be used with caution considering the specific material, other materials that it may or may not be combined with, and any engineering controls and/or process implementation(s) designed for the use of the material in any specific system process. Although certain hazards are described within, these cannot be guaranteed as the only hazards that exist.

Date of issue/Date of revision: 31 July 2020 Version: 4 Page: 16/16